








Alto-Shaam Quickchillers Product Catalog
(as of 11/18/2014 4:43:59 PM)



Specifications subject to change without notice due to ongoing product improvement.

Model	Photo	Description	H x W x D Dimension	Voltage	Pan Capacity	Weight Capacity	Options
QC2-3 Under Counter Blast Chiller 36lb Cap.		Quickchiller™ Blast Chiller, self-contained, undercounter, touch control, HACCP Documentation, temperature probe, timed chill, hold mode with auto defrost cycle, defrost mode, (3) full-size pan capacity, stainless steel interior & exterior, (4) 7" (178mm) legs	39" x 27" x 30" (991mm x 686mm x 762mm)	115v	GN 1/1	36lb (16 kg)	HACCP
QC2-20 Blast Chiller Work Station 60lb Cap.		Quickchiller™ Blast Chiller, self-contained, stainless steel, worktop with backsplash, touch control. HACCP Documentation, temperature probe, timed chill, hold mode with auto defrost cycle, defrost mode, (5) full-size pan capacity, stainless steel interior & exterior, 6" (152mm) legs	42" x 57" x 36" (1067mm x 1448mm x 914mm)	115v 220v	Full-size sheet GN 1/1	60 (27 kg)	HACCP
QC2-40 Reach-In Blast Chiller 240lb Cap.		Quickchiller™ Blast Chiller, reach-in, self-contained, touch control, HACCP Documentation, (3) temperature probes, timed chill, hold mode with auto defrost cycle, defrost mode, with (20) full-size pan capacity, stainless steel interior & exterior, 6" (152mm) legs	75" x 44" x 36" (1905mm x 1118mm x 914mm)	115/208-230v 220v 380-415v 3ph	Full-size sheet GN 1/1	240lb (108kg)	HACCP
QC2-100 Roll In Quick Chiller 240lb Cap.		Quickchiller™ Blast Chiller, roll-in, self-contained with dual refrigeration systems, touch control, HACCP Documentation, (3) product temperature probes, auto chill, timed chill, hold mode with auto defrost cycle & defrost mode; with rack, (40) full-size pan capacity, stainless steel interior & exterior, (4) adjustable legs	93-9/16" x 50-15/16" x 41-1/2" (2377mm x 1294mm x 1054mm)	115/208-230v 1ph 115/208-230v 3ph 220v 1ph 380-415v 3ph	Full-size sheet GN 1/1	480 lb (218 kg)	HACCP Banquet system
QC2-100R Roll In Quick Chiller (Remote Condenser) 240lb Cap.		Quickchiller™ Blast Chiller, roll-in, designed for remote refrigeration systems, touch control, HACCP Documentation, (3) product temperature probes, auto-chill, timed chill, hold mode with auto defrost cycle & defrost mode; with rack, (40) full-size pan capacity, stainless steel interior & exterior, (4) adjustable legs	83-1/4" x 50-15/16" x 41-1/2" (2114mm x 1294mm x 1054mm)	115/208-230v 1ph 220v 1ph 380-415v 3ph	Full-size sheet GN 1/1	480 lb (218 kg)	HACCP Banquet system

Model	Photo	Description	H x W x D Dimension	Voltage	Pan Capacity	Weight Capacity	Options
1000-MR2-1 International Mobile Quickchiller		<p>Only available outside U.S.A.</p> <p>Stainless steel exterior and door, fully insulated with 60 mm of polyurethane. Self-closing lockable door is hinged right as standard and includes a removable magnetic door gasket. The cart is supplied with twenty-four (24) sets of non-tilt pan slides, and three (3) nylon coated shelves.</p> <p>Cart is factory preset to operate between -2°C and +4°C. High ambient (43°C) bottom mounted refrigeration system utilizes R134a refrigerant, generating 1584 BTU (399 KCAL) per hour. A LED display monitors the inside temperature. Audio visual temperature alarms is included as standard, along with HACCP capability, and automatic defrost.</p> <p>Unit includes a full-perimeter bumper guard along with two (2) flush transport handles on each end of the cart.</p> <p>Cart is furnished with four (4) heavy duty swivel casters — two (2) with brake. A 1/4 horsepower compressor system utilizes 404a refrigerant, generating 1815 BTU (457 KCAL) per hour.</p>	68-1/2" x 29-1/2" x 39" (1740mm x 750mm x 990mm)		Full-size sheet GN 1/1		
1000-MR2 Double Cavity International Mobile Quickchiller		<p>Only available outside U.S.A.</p> <p>Double cavity model with 20-gauge, non-magnetic stainless steel exterior and door, fully insulated with high density foamed-in-place polyurethane. Doors include two (2) positive door latches with magnetic-mechanical closing and cylinder door lock. 22-gauge non-magnetic (non-corrosive) stainless steel interior includes four (4) removable stainless steel side racks with 50 shelf positions spaced on 1-1/4" (32mm) centers, six (6) powder coated shelves, 26-1/2" x 21-3/4" (673mm x 552mm). The mobile refrigerator is controlled by one (1) on/off switch, with a factory set temperature of 36°F (2°C). An LED display monitors the inside temperature. Unit includes one (1) transport handle on each end of the cart, and a full-perimeter stainless steel bumper guard. Cart is furnished with removable side racks, six (6) powder coated shelves, six (6) 5" (127mm) heavy duty casters — two (2) rigid and four (4) swivel with brake and rear power cord storage during transport. One (1) 1/3 horsepower compressor system utilizes 134a refrigerant, generating 2560 BTU per hour.</p>	68" x 67-1/2" x 29-1/2" (1727mm x 1714mm x 749mm)		Full-size sheet GN 1/1		